

# Terra 800





# Terra 800



Terra 800 is an all-in-one communications terminal, specifically designed to be utilized in a wide variety of land based applications; such as a dedicated telephone service or a back up emergency telephone system that can be deployed throughout the world.

Featuring an intelligent RJ11/POTS interface to enable connection of up to 5 standard corded/cordless phones or integration to a PABX system, supporting cable runs of up to 600m (2000') and presents standard ring, busy and dial tones.

The Terra 800 has an integrated Bluetooth for voice communications, intuitive color LCD display that provides easy and convenient access to send and receive SMS or to retrieve phone numbers stored in the terminal.

Other key features include, a secondary SIM socket to override internal SIM, an active privacy handset, in-built handsfree speakerphone, USB data, inbuilt phone book, SMS, adjustable ring tones, desk or wall mountable.

The Terra 800 is designed to operate with the Inmarsat "Link Phone" service and is supplied with a dedicated high quality directional/fixed antenna system to provide a completely integrated solution that is ready for use anytime.

















Mute



SIM



LCD Display



POTS/RJ11



USB



Privacy Handset



Handsfree



Remote Work Sites



Disaster Recovery



Remote School Communications



Farm Houses

## **KEY FEATURES**

#### DESIGN

- High quality IP54 rated enclosure
- Colour LCD Screen
- Compact all in one design
- Wall or desk mounting options
- Locking bolt to wall mounting
- Accessible control buttons
- Integrated antenna connections
- Slimline privacy handset
- In-built speakerphone
- Cable routing LHS/TOP/BOTTOM
- Dual SIM card enclosures

#### POWER

- 10-32V DC Input
- 110/240V AC plug pack, included

### INTELLIGENT POTS/RJ11 INTERFACE

- Support up to 600m (2000') of RJ11 cable runs
- Standard dial, ring & busy tones
- Integrates easily to PABX System
- Support standard corded, cordless and DECT phones
- Auto-dial & speed dials available

#### VOICE CALLING FEATURES

- Integrated easy to use phone book
- Privacy handset calling
- In-built handsfree speakerphone
- Access from PBX or other corded/cordless handsets
- Bluetooth headsets (not included)

#### OTHER KEY FEATURES

- SMS
- Secondary and over riding accessible SIM port (credit card sized SIM)
- Phonebook
- Status LED
- Adjustable brightness
- USB data access

## **TECHNICAL SPECIFICATIONS**

Model: TR800

AVERAGE POWER CONSUMPTION (Passive Antenna Connected)	CURRENT @ 15V AVERAGE	POWER
Standby	0.17 A	2.6 W
Transmit (RJ11/POTS call)	0.31 A	4.7 W
Transmit (Spreakerphone)	0.27 A	4.0 W
Peak Current	0.70 A	10.5 W
PHYSICAL SPECIFICATIONS		
Dimensions	241 x 185 x 93 (mm)	9.49 x 7.28 x 3.66 (inches)
Weight TR800 Only	1.27kg	2.80lb
ENVIRONMENT SPECIFICA	TIONS	
Operation	-20°C to +55°C	-4°F to +131°F
Storage	-30°C to +80°C	-22°F to +176°F
Humidity	<=75% RH	
TRANSCEIVER		
Inmarsat - 4 Satellite GMR - 2+ Frequency Bands		
Tx Operating Frequency	1626.5 - 1660.5 MHz	
Rx Operating Frequency	1518 - 1565 MHz (Inmarsat) 1565.19 - 585.65 MHz (GPS)	
RF Output Impedance	50 Ohms	
Carrier Frequencies	Channel 0 = 1626.525 MHz Channel 169 = 1660.475 MHz	
TX Modulation	GMSK	
RX Modulation	OQPSK	
CONNECTORS / INTERFACES		
POTS/RJ11	RJ11/2-wire, 5REN @ 600m, Adjustable dial, ring, busy tone configured frequency and adaptive impedance.	
Inmarsat Antenna	TNC-Female	
GPS Antenna	SMA-Female	
10-32 V DC	4-way microFit (AC/DC adator, or DC lead)	

RJ9 connector		
USB Mini B		
built speaker/microphone		
CERTIFICATIONS		
Inmarsat, FCC, CE Compliance, Electrical Safety, RoHS, Industry Canada, C-Tick		
IP54 Rating 5 = Protected against dust limited ingress (no harmful deposits). 4 = Protection against water sprayed from all directions - limited ingress permitted.		
KIT CONTENTS		
Terra 800		
ISD700 Directional/Fixed Antenna (Passive)		
Privacy Handset		
110 - 240V AC Plug Pack 15v DC Out		
10 - 32V DC Power Cable		
1 x Spring cup (attached to terminal)		
1 x Springless cup		
USB Cable		
2m Alert wiring loop		
Wall mounting plate		
User manual		
Quick Start Guide		
ACCESSORIES		
ne - www.leotrak.com		
n SMA/TNC cable kit (Passive)		
20m SMA/TNC cable kit (Passive)		
BOm SMA/TNC cable kit (Passive)		
n SMA/TNC cable kit (Passive)		
n SMA/TNC cable kit (Passive) n SMA/TNC cable kit (Passive)		
,		

APPROVED BEAM RESELLER

www.beamcommunications.com



+61 3 8588 4500



+61 3 9560 9055



info@beamcommunications.com

ASIA AUSTRALIA

EUROPE

MIDDLE EAST

NORTH AMERICA

SOUTH AMERICA